

Safety Data Sheet

8500-HE-C40-80 gh3

1. Product and company identification

Product name : 8500-HE-C40-80 gh3
Material uses : Petrochemical industry: Fuel additive.
Internal code : IFS0607
System code : IFS0607
Supplier : Innospec Fuel Specialties LLC
 8310 South Valley Highway
 Suite 350
 Englewood
 CO, 80112
 USA

Information contact : 1-800-441-9547
e-mail address of person responsible for this SDS : sdsinfo@innospecinc.com
NON-emergency enquiries : corporatecommunications@innospecinc.com

Emergency telephone number

In USA, Canada and North America, 24 hour / 7 day emergency information for our product is provided by the CHEMTREC® Emergency Call Center based in the USA

Country information : Emergency telephone number

USA, Canada, Puerto Rico, Virgin Islands : +1 800 424 9300

In case of difficulties, or for ships at sea : +1 703 527 3887

In Europe, Middle East, Africa, Asia Pacific and South America 24 hour / 7 day emergency response for our products is provided by the NCEC CARECHEM 24 global network




The main regional centres are listed here in Section 1.

Other local contact numbers for specific language support in Asia Pacific are listed in Section 16

Country information	: Emergency telephone number	Location
South America (all countries)	: +1 215 207 0061	Philadelphia USA
Brazil	: +55 11 3197 5891	Brazil
Mexico	: +52 555 004 8763	Mexico
Europe (all countries) Middle East, Africa (French, Portuguese, English)	: +44 (0) 1235 239 670	London, UK
Middle East, Africa (Arabic, French, English)	: +44 (0) 1235 239 671	Lebanon
Asia Pacific (all countries except China)	: +65 3158 1074	Singapore
China	: +86 10 5100 3039	Beijing China

Date of issue/Date of revision : 2016-02-12

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: <ul style="list-style-type: none"> ☑ FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1
<u>GHS label elements</u>	
Hazard pictograms	: <div style="text-align: center;">  </div>
Signal word	: ☑ Danger
Hazard statements	: <ul style="list-style-type: none"> ☑ H226 - Flammable liquid and vapor. H302 + H332 - Harmful if swallowed or if inhaled. H315 + H320 - Causes skin and eye irritation. H351 - Suspected of causing cancer. H304 - May be fatal if swallowed and enters airways.
<u>Precautionary statements</u>	
Prevention	: <ul style="list-style-type: none"> P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P281 - Use personal protective equipment as required. P280 - Wear protective gloves. Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P233 - Keep container tightly closed. P271 - Use only outdoors or in a well-ventilated area. P261 - Avoid breathing vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling.
Response	: <ul style="list-style-type: none"> ☑ P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P340 + P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P302 + P352 + P362-2 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. P332 + P313 - If skin irritation occurs: Get medical attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.

Section 2. Hazards identification

Storage	: P405 - Store locked up. P403 - Store in a well-ventilated place. P235 - Keep cool.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.
Target organs	: Contains material which causes damage to the following organs: blood, kidneys, liver, lymphatic system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea. Contains material which may cause damage to the following organs: the nervous system, gastrointestinal tract, cardiovascular system, ears.

See toxicological information (Section 11)

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Xylene	60 - 100	1330-20-7
ethylbenzene	15 - 30	100-41-4
2-butoxyethanol; butyl cellosolve	0.99 - 4.99	111-76-2
Solvent naphtha (petroleum), heavy arom.	0.99 - 4.99	64742-94-5
naphthalene	0.09 - 0.99	91-20-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Contains <15% 2-ethylhexyl nitrate [CAS 27247-96-7]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 2016-02-12

Section 4. First aid measures

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact : Causes skin irritation.

Ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Date of issue/Date of revision : 2016-02-12

4/15

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fight fire from protected location or maximum possible distance. Cool containing vessels with flooding quantities of water until well after fire is out.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Flash point** : Closed cup: 30°C (86°F) [Pensky-Martens.]

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 8. Exposure controls/personal protection

2-butoxyethanol; butyl cellosolve	<p>NIOSH REL (United States, 10/2013). TWA: 100 ppm, 0 times per shift, 10 hours. TWA: 435 mg/m³, 0 times per shift, 10 hours. STEL: 125 ppm, 0 times per shift, 15 minutes. STEL: 545 mg/m³, 0 times per shift, 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 100 ppm, 0 times per shift, 8 hours. TWA: 435 mg/m³, 0 times per shift, 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 25 ppm, 0 times per shift, 8 hours. TWA: 120 mg/m³, 0 times per shift, 8 hours.</p>
naphthalene	<p>NIOSH REL (United States, 10/2013). Absorbed through skin. TWA: 5 ppm, 0 times per shift, 10 hours. TWA: 24 mg/m³, 0 times per shift, 10 hours.</p> <p>ACGIH TLV (United States, 4/2014). TWA: 20 ppm, 0 times per shift, 8 hours.</p> <p>OSHA PEL (United States, 2/2013). Absorbed through skin. TWA: 50 ppm, 0 times per shift, 8 hours. TWA: 240 mg/m³, 0 times per shift, 8 hours.</p> <p>ACGIH TLV (United States, 3/2015). Absorbed through skin. TWA: 10 ppm, 0 times per shift, 8 hours. TWA: 52 mg/m³, 0 times per shift, 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 10 ppm, 0 times per shift, 8 hours. TWA: 50 mg/m³, 0 times per shift, 8 hours. STEL: 15 ppm, 0 times per shift, 15 minutes. STEL: 75 mg/m³, 0 times per shift, 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 10 ppm, 0 times per shift, 10 hours. TWA: 50 mg/m³, 0 times per shift, 10 hours. STEL: 15 ppm, 0 times per shift, 15 minutes. STEL: 75 mg/m³, 0 times per shift, 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 10 ppm, 0 times per shift, 8 hours. TWA: 50 mg/m³, 0 times per shift, 8 hours.</p>

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Yellow. to Amber.
- Odor** : Aromatic.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Lowest known value: 136.05°C (276.9°F) (ethylbenzene). Weighted average: 140.62°C (285.1°F)
- Flash point** : Closed cup: 30°C (86°F) [Pensky-Martens.]
- Evaporation rate** : Highest known value: <1 (2-ethylhexyl nitrate) Weighted average: 0.75 compared with butyl acetate
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Greatest known range: Lower: 1.1% Upper: 10.6% (2-butoxyethanol)
- Vapor pressure** : Highest known value: 1.2 kPa (9.3 mm Hg) (at 20°C) (ethylbenzene). Weighted average: 0.79 kPa (5.93 mm Hg) (at 20°C)

Section 9. Physical and chemical properties

Vapor density	: Highest known value: 4.6 to 5.5 (Air = 1) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 3.59 (Air = 1)
Specific gravity	: 0.883 [ASTM D 4052]
Density	: 7.35 lbs/gal
Solubility	: Partially soluble in the following materials: cold water, hot water.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Lowest known value: 176°C (348.8°F) (2-ethylhexyl nitrate).
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): 0.01 cm ² /s (1 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: This mixture contains materials which are unstable under the following conditions: heat Incompatible with fluorine.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Species	Result	Dose
xylene	-	Rabbit	LD50 Dermal	4320 mg/kg
	-	Rat	LD50 Oral	4300 mg/kg
ethylbenzene	-	Mouse	LC50 Inhalation Vapor	35500 mg/m ³
	-	Rabbit	LC50 Inhalation Vapor	4000 ppm
2-butoxyethanol	-	Rabbit	LD50 Dermal	>5000 mg/kg
	-	Rat	LD50 Oral	250 mg/kg
	-	Rat	LC50 Inhalation Vapor	>590 mg/m ³
Solvent naphtha (petroleum), heavy arom.	-	Rabbit	LD50 Dermal	>2 mL/kg
	-	Rabbit	LD50 Dermal	2000 mg/kg
naphthalene	-	Rat	LDLo Oral	5 mL/kg
	-	Rat	LC50 Inhalation Vapor	>340 mg/m ³
	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LD50 Dermal	>2500 mg/kg
	-	Rat	LD50 Oral	490 mg/kg

Potential chronic health effects

Not available.

Section 11. Toxicological information

Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Xylene	-	Rabbit	Eyes - Severe irritant -
	-	Rat	Skin - Mild irritant -
	-	Rabbit	Skin - Moderate irritant -
ethylbenzene	-	Rabbit	Eyes - Severe irritant -
	-	Rabbit	Skin - Mild irritant -
2-butoxyethanol	-	Rabbit	Eyes - Moderate irritant -
	-	Rabbit	Eyes - Severe irritant -
	-	Rabbit	Skin - Mild irritant -
Solvent naphtha (petroleum), heavy arom.	-	Rabbit	Skin - Mild irritant -
	-	Mammal - species unspecified	Eyes - Mild irritant -

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
Xylene	-	3	-
ethylbenzene	-	2B	-
2-butoxyethanol; butyl cellosolve	-	3	-
naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), heavy arom.	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Xylene	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), heavy arom.	ASPIRATION HAZARD - Category 1

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Xylene ethylbenzene	Acute LC50 3.3 mg/l	Fish	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
2-butoxyethanol; butyl cellosolve	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 7.2 mg/l	Algae	48 hours
Solvent naphtha (petroleum), heavy arom.	Acute EC50 2.93 mg/l	Daphnia	48 hours
	Acute LC50 4.2 mg/l	Fish	96 hours
naphthalene	Chronic NOEC <1000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC 6800 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
2-butoxyethanol; butyl cellosolve	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1490 mg/l	Fish	96 hours
Solvent naphtha (petroleum), heavy arom.	Chronic NOEC 1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1 to 3 mg/l	Algae	72 hours
naphthalene	Acute EC50 3 to 10 mg/l	Daphnia	48 hours
	Acute LC50 2 to 5 mg/l	Fish	96 hours
naphthalene	Acute EC50 1.96 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 1.6 mg/l	Fish	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Xylene	-	-	Readily
ethylbenzene	-	-	Readily
Solvent naphtha (petroleum), heavy arom.	-	-	Inherent

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	3.12 to 3.2	8.1 to 25.9	low
ethylbenzene	3.1	-	low
2-butoxyethanol; butyl cellosolve	0.83	-	low
Solvent naphtha (petroleum), heavy arom.	-	<100	low
naphthalene	3.3	>100	low




Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product

Section 13. Disposal considerations

residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN1993	UN1993	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (xylene, ethylbenzene) RQ (Xylene, Ethylbenzene)	FLAMMABLE LIQUID, N.O.S. (xylene, ethylbenzene)	Flammable liquid, n.o.s. (xylene, ethylbenzene)
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	No.	No.	No.
Additional information	<p>Reportable quantity 154.69 lbs / 70.23 kg [21.011 gal / 79.536 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.</p> <p>Limited quantity Yes.</p> <p>Packaging instruction Passenger aircraft Quantity limitation: 60 L</p> <p>Cargo aircraft Quantity limitation: 220 L</p> <p>Special provisions B1, B52, IB3, T4, TP1, TP29</p>	<p>Emergency schedules (EmS) F-E, _S-E_</p> <p>Special provisions 223, 274, 955</p>	<p>Passenger and Cargo Aircraft Quantity limitation: 60 L Packaging instructions: 355</p> <p>Cargo Aircraft Only Quantity limitation: 220 L Packaging instructions: 366</p> <p>Limited Quantities - Passenger Aircraft Quantity limitation: 10 L Packaging instructions: Y344</p> <p>Special provisions A3</p>

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations : United States inventory (TSCA 8b): All components are listed or exempted.
Clean Water Act (CWA) 307: ethylbenzene; naphthalene; toluene

Clean Air Act Section 112 : Listed
(b) Hazardous Air Pollutants (HAPs)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Fire hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Xylene	60 - 100	Yes.	No.	No.	Yes.	No.
ethylbenzene	15 - 30	Yes.	No.	No.	Yes.	Yes.
2-butoxyethanol; butyl cellosolve	0.99 - 4.99	Yes.	No.	No.	Yes.	No.
Solvent naphtha (petroleum), heavy arom.	0.99 - 4.99	Yes.	No.	No.	Yes.	No.
naphthalene	0.09 - 0.99	No.	No.	No.	Yes.	Yes.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Xylene	1330-20-7	60 - 100
	ethylbenzene	100-41-4	15 - 30
	2-butoxyethanol	111-76-2	0.99 - 4.99
	naphthalene	91-20-3	0.09 - 0.99
Supplier notification	Xylene	1330-20-7	60 - 100
	ethylbenzene	100-41-4	15 - 30
	2-butoxyethanol	111-76-2	0.99 - 4.99
	naphthalene	91-20-3	0.09 - 0.99

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: 2-BUTOXYETHANOL; XYLENE
New York : The following components are listed: Xylene (mixed); Naphthalene
New Jersey : The following components are listed: 2-BUTOXY ETHANOL; BUTYL CELLOSOLVE; XYLENES; BENZENE, DIMETHYL-; NAPHTHALENE; MOTH FLAKES
Pennsylvania : The following components are listed: ETHANOL, 2-BUTOXY-; BENZENE, DIMETHYL-; NAPHTHALENE
California Prop. 65

Date of issue/Date of revision : 2016-02-12

13/15

Section 15. Regulatory information

: WARNING: This product contains a chemical known to the State of California to cause cancer.

WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level	Contains : % or ppm
ethylbenzene	Yes.	No.	41 µg/day (ingestion) 54 µg/day (inhalation)	No.	15 - 30
naphthalene	Yes.	No.	Yes.	No.	0.09 - 0.99
toluene	No.	Yes.	No.	7000 µg/day (ingestion) 13000 µg/day (inhalation)	<1ppm
cumene	Yes.	No.	No.	No.	<1ppm

International lists

National inventory

Australia inventory (AICS)

Canada inventory

China inventory (IECSC)

Europe inventory

Japan inventory (ENCS)

New Zealand Inventory of Chemicals (NZIoC)

Philippines inventory (PICCS)

Korea inventory (KECI)

Taiwan inventory (TCSI)

United States inventory (TSCA 8b)

- : Not determined.
- : All components are listed or exempted.
- : At least one component is not listed.
- : At least one component is not listed in EINECS but all such components are listed in ELINCS.
Please contact your supplier for information on the inventory status of this material.
- : At least one component is not listed.
- : All components are listed or exempted.
- : At least one component is not listed.
- : At least one component is not listed.
- : All components are listed or exempted.
- : All components are listed or exempted.

Our REACH (pre-) registrations DO NOT cover the following:

1. The manufacture of these products by our company outside the EU unless covered by the Only Representative provisions, and
 2. The importation of these products into Europe by other companies. Re-importation by other companies is not covered by our (pre-) registrations
- Customers and other third parties importing and/or re-importing our products into Europe will need either:
- Their own (pre-) registration for substances contained in the imported product, or constituent monomers (imported above 1 tonne per year and >2% by weight) in the case of imported polymers, or
 - In the case of importation only, to make use of the "Only Representative" provisions, if available.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Classification according to Directive 67/548/EEC [DSD] or Classification according to Directive 1999/45/EC [DPD]

Risk phrases : R10- Flammable.
R20/21- Harmful by inhalation and in contact with skin.
R38- Irritating to skin.
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S36/37- Wear suitable protective clothing and gloves.

History

Date of printing : 2016-02-12

Date of issue/Date of revision : 2016-02-12

Date of previous issue : 2015-05-18

Version : 1.02

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

☑ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 2016-02-12